

Semi-Professional

200 Fixgen Tile Adhesive is a dry entry-line polymer modified thin-set mortar used in the installation of tiles and stones over floors & walls. This mortar is recommended for most interior and exterior residential uses as well as light interior commercial uses.



Characteristics:

- ❖ Polymer Modified
- ❖ Good shear bond strength
- ❖ Excellent grip for porcelain tiles
- ❖ Smooth creamy formula
- ❖ Good workability
- ❖ Easy to use
- ❖ Can be used indoors and outdoors
- ❖ Best price/quality ratio

Recommended Substrates:

Cured concrete
Masonry blocks
Gypsum plaster
Existing bricks
Gypsum wallboard (with Admix 60.)
Cement backer-board
Terrazzo floors
Existing unglazed floor tiles (with Admix 6.)

Packaging:

20 kgs.

Colour: Gray

Coverage:

Approximately 50 to 60 sq.ft per 20 kg bag with 6 mm x 6 mm square notch trowel for bed thickness of 3mm. Usage requirements are approximate. Coverage will depend on the trowel used and the condition of the subfloor.

Technical data:



Bed thick 3-12 mm



Open time 30-40 min



Pot life 3-4 hr



Interior & Exterior



Wall & floor

Size	Notch Trowel Size	Coverage Per Bag
8" - 12"	6mmx6mm	60sq.ft.
12" - above	10mmx10mm	50sq.ft.

Coverage approximately

Recommended for

VITRIFIED TILE
PORCELAIN TILE

